

MMC Loopback

Basic characteristics

- ▲ Product diagnostic/field testing
- ▲ Device burn-in
- ▲ Allows testing of optical network segment by segment
- ▲ DirectConec™ push-pull boot



Temperature range

Indoor controlled environment (-10°C/+60°C)

Cable parameters

Jacket material	OFNP or LSZH	
Cable construction	Round single jacket cable	
Outer diameter	2.3mm	
Fiber count	16 Fibers	
Fiber type	SM OS2 or MM OM3/OM4	
Temperature range	operation:	0°C/+70°C
	storage:	-40°C/+70°C
	installation:	-10°C/+60°C

Connector parameters

	MMC SM	MMC MM
Compliance	US CONEC standard	US CONEC standard
Color of housing	Green	Green
Color of boot	Black	Black
Polish	Angled (APC)	Angled (APC)
Insertion Loss (acc. IEC 61300-3-4 method B)	<0,7dB (@1310/1550nm)	<0,7dB (@850/1300nm)

Identification

Traceability label with unique serial number.

Packaging

Each assembly in sealed PE bag, bulk pack in cardboard box.

MMC is a registered trademark of US CONEC, Ltd.

* Specifications are subject to change without notice

**For more information contact our sales team
at sales@sylex.sk**