



- 1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN
- 2 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM
- 3 - OM4 - IL<0.35dB, RL>20dB, 850nm & 1300nm  
OS2 - IL<0.35dB, RL>50dB, 1310nm & 1550nm  
IL CONNECTOR VALUE ACCORDING IEC 61300-3-4 method B  
RL CONNECTOR VALUE ACCORDING IEC 61300-3-6
- 4 - VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35  
END FACE GEOMETRY ACCORDING TO IEC 61755-3-31 (Multifiber connector - APC polished)  
END FACE GEOMETRY ACCORDING TO IEC 63267-3-31 (Multifiber connector - FLAT polished)
- 5 - ASSEMBLY WITH LENGTH BELOW 50MTRS PACKED IN SEALED PE BAG, BULK PACK IN OUTER CARDBOARD BOX.  
LONGER ASSEMBLY THEN 50MTRS COILED ON WOODEN REEL [1-S-8277](#)
- 6 - CABLE LENGTH TOLERANCES AND FANOUT LENGTH TOLERANCES ACCORDING TO SYLEX STANDARD [1-S-8000](#)
- 7 - TRACEABILITY LABEL ON THE CABLE CONTAINS SERIAL NUMBER, DATE OF PRODUCTION AND ASSEMBLY LENGTH
- 8 - TYPE OF POLARITIES ACCORDING TO [SPECIFICATION](#)
- 7 - PULLING SYSTEM FROM BLACK TUBE IS ON BOTH SIDES OF THE ASSEMBLY (NOT SHOWN)  
OUTER DIAMETER OF THE PULLING TUBE IS 34,8mm
- 10 - FOR THE FIXATION OF THE PRODUCT TO THE 1U PANEL IT IS NECESSARY TO USE ACCESSORIES

### ORDERING CODE

X12X-XXX-xxx

- xxx cable length [050 = 50m, 001 = 1m]
- A - Polarity A, B - Polarity B, C - Polarity C
- F MTP(F) 12F, M MTP(M) 12F,  
J MTP(F) PRO 12F, P MTP(M) PRO 12F
- F MTP(F) 12F, M MTP(M) 12F,  
J MTP(F) PRO 12F, P MTP(M) PRO 12F
- 9 OS2, 4 OM4 \*
- 12 12F
- Q U-DQ preterm

\* OM3, OM5 ONLY ON REQUEST

|                             |         |  |  |                                   |                 |
|-----------------------------|---------|--|--|-----------------------------------|-----------------|
| REVISION-DATE: A-06.10.2023 | CHANGE: | DRAWN BY, DATE: M.Ruzbarsky 2023/06/10     | TITLE: 12f 1xMTP - 1xMTP U-DQ FLEXX Trunk  |                                   |                 |
| New drawing                 |         | CHECKED BY, DATE: M.Bombarova 2023/06/10   |  |                                   |                 |
| REVISION-DATE:              | CHANGE: | APPROVED BY, DATE: Matus/Smelh. 2023/06/10 | PRODUCT SPECIFICATION: QPN - 000   | DIMENSIONS IN MM UNLESS SPECIFIED | SCALE: NO SCALE |
| REVISION-DATE:              | CHANGE: | PRODUCT NUMBER: Q12X-XXX-xxx               | DRAWING NUMBER: 1-W-9585_1_A   | SHEET NO.: 1 of 1                 |                 |
|                             |         | A  | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SYLEX S.r.l. AND ANY USE WITHOUT PRIOR WRITTEN PERMISSION IS PROHIBITED |                                   |                 |
|                             |         |  |  | SIZE: A3                          |                 |