



NOTES :

- 1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN
- 2 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM
- 3 - OM3, OM4 - IL<0.35dB , RL>50dB , 850nm & 1300nm
OS2 - IL<0.35dB, RL>50dB, 1310nm & 1550nm
IL CONNECTOR VALUE ACCORDING IEC 61300-3-4 method B
RL CONNECTOR VALUE ACCORDING IEC 61300-3-6
- 4 - VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35.
END FACE GEOMETRY ACCORDING TO IEC 61755-3-31
- 5 - ASSEMBLY WITH LENGTH BELOW 50MTRS PACKED IN SEALED PE BAG,
BULK PACK IN OUTER CARDBOARD BOX.
LONGER ASSEMBLY THEN 50MTRS COILED ON CARDBOARD REEL,
INSERTED IN CARDBOARD BOX ACCORDING TO SYLEX STANDARD [1-S-0011](#)
- 6 - CABLE LENGTH TOLERANCES AND FANOUT LENGTH TOLERANCES
ACCORDING TO SYLEX STANDARD [1-S-8000](#)
- 7 - TRACEBILITY LABEL ON THE CABLE CONTAINS SERIAL NUMBER,
DATE OF PRODUCTION AND ASSEMBLY LENGTH
- 8 - TYPE OF POLARITIES ACCORDING TO [SPECIFICATION](#)

ORDERING CODE

P16X-XXX-xxx

- xxx cable length [050 = 50m, 001 = 1m]
- A - Polarity A, B - Polarity B
- 6 MTP(F) 16F, 7 MTP(M) 16F
- 6 MTP(F) 16F, 7 MTP(M) 16F
- 9 OS2, 3 OM3, 4 OM4
- 16 16F
- P Patch cable

| | | | | | |
|-------------------------------|---------|--|---|-----------------------------------|------------------|
| REVISION-DATE: A - 30.09.2020 | CHANGE: | DRAWN BY, DATE: M.Ruzbarsky 2020/09/30 | TITLE: 16f 1xMTP/APC - 1xMTP/APC Patch cable | | |
| New drawing | | CHECKED BY, DATE: Matus/Smelh. | | | |
| REVISION-DATE: | CHANGE: | APPROVED BY, DATE: L.Miskerik | PRODUCT SPECIFICATION: - | DIMENSIONS IN MM UNLESS SPECIFIED | SCALE: NO SCALE |
| REVISION-DATE: X - DD.MM.YYYY | CHANGE: | | PRODUCT NUMBER: P16X-XXX-xxx-X | DRAWING NUMBER: 1-W-8058_1_A | SHEET NO. 1 of 1 |
| | | | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SYLEX s.r.o AND ANY USE WITHOUT PRIOR WRITTEN PERMISSION IS PROHIBITED | | SIZE A3 |