

sylex®
FIBER OPTICS

NOTES :

- 1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN
- 2 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM
- 3 - OM3, OM4, OM5 - IL<0.25dB , RL>30dB , 850nm & 1300nm
OS2 - IL<0.25dB, LC/APC - RL>60dB, 1310nm & 1550nm
LC/UPC - RL>50dB, 1310nm & 1550nm
IL CONNECTOR VALUE ACCORDING IEC 61300-3-4 method B
RL CONNECTOR VALUE ACCORDING IEC 61300-3-6
- 4 - VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35.
END FACE GEOMETRY ACCORDING TO TELCORDIA GR-326
- 5 - CABLE LENGTH TOLERANCES AND FANOUT LENGTH TOLERANCES ACCORDING TO SYLEX STANDARD [1-S-8000](#)
- 6 - TRACEBILITY LABEL ON THE CABLE CONTAINS SERIAL NUMBER, DATE OF PRODUCTION AND ASSEMBLY LENGTH
- 7 - SET OF 12 PIGTAILS CONTAINS PIGTAILS WITH 12 DIFFERENT CABLE COLORS


ORDERING CODE

CXXX-XX1-xxx

- xxx cable length [050 = 50m, 001 = 1m]
- 1 SIMPLEX CONNECTOR
- L LC/UPC, A LC/APC *
- 9 OS2, 3 OM3, 4 OM4, 5 OM5
- 9 0.9mm, 2 2.0mm, 3 3.0mm **
- 1 SIMPLEX, S SET 12x 900um
- C Cord

* OTHER CONNECTOR TYPES ON REQUEST

** OTHER CABLE TYPES ON REQUEST

REVISION-DATE: A - 28.10.2019	CHANGE:	DRAWN BY, DATE: P. Gašpár 2019/10/28	TITLE: 1f Simplex Pigtail		
New drawing		CHECKED BY, DATE: Pavlov/Matúš			
REVISION-DATE:	CHANGE:	APPROVED BY, DATE: I. Brestovanská	PRODUCT SPECIFICATION: -	DIMENSIONS IN MM UNLESS SPECIFIED	SCALE: NO SCALE
REVISION-DATE: X - DD.MM.YYYY	CHANGE:		PRODUCT NUMBER: CXXX-XX1-xxx	DRAWING NUMBER: 1-S-7403_1_A	SHEET NO. 1 of 1
		A	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SYLEX s.r.o AND ANY USE WITHOUT PRIOR WRITTEN PERMISSION IS PROHIBITED		
				SIZE A3	