

SAA-01 SingleAxis Acelerometer
Measurement range ±200g, Temperature range -20°C to +60°C

Ordering information			Installation information		
WL configuration	WL type	Nominal WL @ 22,5°C (after production)	WL @ -200g @ -20°C	WL @ 0g @ 22,5°C	WL @ 200g @ 60°C
A	ACC	1 516,5nm	1 512,5nm	1 516,5nm	1 520,4nm
B	ACC	1 524,5nm	1 520,5nm	1 524,5nm	1 528,4nm
C	ACC	1 532,5nm	1 528,5nm	1 532,5nm	1 536,4nm
D	ACC	1 540,5nm	1 536,5nm	1 540,5nm	1 544,4nm
E	ACC	1 548,5nm	1 544,5nm	1 548,5nm	1 552,4nm
F	ACC	1 556,5nm	1 552,5nm	1 556,5nm	1 560,4nm
G	ACC	1 564,5nm	1 560,5nm	1 564,5nm	1 568,4nm
H	ACC	1 572,5nm	1 568,5nm	1 572,5nm	1 576,4nm
I	ACC	1 580,5nm	1 576,5nm	1 580,5nm	1 584,4nm

Example of standard stock available WL configurations and their chaining possibilities in one optical channel.
Other WL's on demand