

LC-LC 72-fiber Duralino trunk, free tails simplex tubing

Basic characteristics

- ▲ Durable material
- ▲ Compact
- ▲ Light weight



Benefits

- ▲ Compact design of cable – outer diameter 5,5-6,3mm
- ▲ Durable metal fan-out

Applications

- ▲ DataCenter cabling
- ▲ Inside building interconnections
- ▲ Direct patching of ODFs

Temperature range

Controlled environment (-10°C/+60°C)

Cable parameters

Jacket material	LSZH	
Cable construction	Micro-Bundle	
Outer diameter	5,5-6,3mm	
Fiber count	72	
Fiber type	SM OS2 or MMF OM3/OM4	
Temperature range	operation:	-10°C to +60°C
	storage:	-20°C to +60°C
	installation:	0°C to +40°C

LC-LC 72-fiber Duralino trunk, free tails simplex tubing

Connector parameters

	LC SM	LC MM
Compliance	Telcordia GR-326	Telcordia GR-326
Color of housing	Blue (UPC)/Green (APC)	Aqua/Magenta
Color of boot	White (UPC) or Green (APC)	White
Polish	Flat (UPC) or Angled (APC)	Flat (PC)
Insertion Loss	<0,25dB	<0,25dB
Return Loss	>50dB (UPC)/>60dB (APC)	>30dB

Identification

Traceability label with unique serial number on both ends of cable assembly.

Packaging

Each assembly in plastic bag, bulk pack in cardboard box.
Longer lengths coiled on cardboard reel.

* Specifications are subject to change without notice

For more information contact our sales team at sales@sylex.sk