

## LC-LC 96-fiber Duralino trunk, free tails simplex tubing

### Basic characteristics

- ▲ Durable material
- ▲ Compact
- ▲ Light weight



### Benefits

- ▲ Compact design of cable – outer diameter 6,4-7,5mm
- ▲ Durable metal fan-out

### Applications

- ▲ DataCenter cabling
- ▲ Inside building interconnections
- ▲ Direct patching of ODFs

### Temperature range

Controlled environment (-10°C/+60°C)

### Cable parameters

Jacket material	LSZH	
Cable construction	Micro-Bundle	
Outer diameter	6,4-7,5mm	
Fiber count	96	
Fiber type	SM OS2 or MMF OM3/OM4	
Temperature range	operation:	-10°C to +60°C
	storage:	-20°C to +60°C
	installation:	0°C to +40°C

## LC-LC 96-fiber Duralino trunk, free tails simplex tubing

### Connector parameters

	LC SM	LC MM
Compliance	Telcordia GR-326	Telcordia GR-326,
Color of housing	Blue (UPC)/Green (APC)	Aqua/Magenta
Color of boot	White (UPC) or Green (APC)	White
Polish	Flat (UPC) or Angled (APC)	Flat (PC)
Insertion Loss	<0,25dB	<0,25dB
Return Loss	>50dB (UPC)/>60dB (APC)	>30dB

### Identification

Traceability label with unique serial number on both ends of cable assembly.

### Packaging

Each assembly in plastic bag, bulk pack in cardboard box.  
Longer lengths coiled on cardboard reel.

\* Specifications are subject to change without notice

For more information contact our sales team at [sales@sylex.sk](mailto:sales@sylex.sk)