

## MTP CXP/CFP to MTP QSFP fanout

### Basic characteristics

- ▲ Complete fiber optic interconnection links for active devices
- ▲ 3x40Gbit parallel transmission over 1 cable
- ▲ Laser optimised MM bend insensitive fiber
- ▲ MTP® PRO connector optional



### Temperature range

Indoor controlled environment (-10°C/+60°C)

### Cable parameters

Jacket material	LSZH	
Cable construction	Round cable	
Outer diameter	3,8mm	
Fiber count	24	
Fiber type	MMF OM3/OM4	
Temperature range	operation:	-10°C to +70°C
	storage:	-25°C to +70°C
	installation:	-5°C to +50°C
CPR	Cca-s1a, d1, a1 B2ca-s1a, d1, a1	

### Connector parameters

	24F MTP®/MTP® PRO	12F MTP®/MTP® PRO
Compliance	US CONEC standard	US CONEC standard
Colour of housing	Aqua/Magenta	Aqua/Magenta
Colour of boot	Black	Black
Polish	Flat (PC)	Flat (PC)
Insertion Loss (acc. IEC 61300-3-4 method B)	<0,35dB (@850/1300nm)	<0,35dB (@850/1300nm)
Return Loss (acc. IEC 61300-3-6)	>20dB (@850/1300nm)	>20dB (@850/1300nm)

### Identification

Traceability label with unique serial number on both ends of cable assembly.

### Packaging

Each assembly in sealed PE bag, bulk pack in cardboard box. Longer lengths coiled on cardboard/wooden reel.

MTP is a registered trademark of US Conec, Ltd.  
\* Specifications are subject to change without notice

MTP CXP/CFP to MTP QSFP fanout

For more information contact our sales team at [sales@sylex.sk](mailto:sales@sylex.sk)