



**NOTES :**

- 1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN
- 2 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM
- 3 - OM3, OM4, OM5 - IL<0.35dB , RL>20dB , 850nm & 1300nm  
OS2 - IL<0.35dB, RL>50dB, 1310nm & 1550nm  
IL CONNECTOR VALUE ACCORDING IEC 61300-3-4 method B  
RL CONNECTOR VALUE ACCORDING IEC 61300-3-6
- 4 - VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35  
END FACE GEOMETRY ACCORDING TO IEC 61755-3-31 (Multifiber connector - APC polished)  
END FACE GEOMETRY ACCORDING TO IEC 63267-3-31 (Multifiber connector - FLAT polished)
- 5 - ASSEMBLY WITH LENGTH BELOW 50MTRS PACKED IN SEALED PE BAG,  
BULK PACK IN OUTER CARDBOARD BOX.  
LONGER ASSEMBLY THEN 50MTRS COILED ON CARDBOARD REEL,  
INSERTED IN CARDBOARD BOX ACCORDING TO SYLEX STANDARD [1-S-0011](#)
- 6 - CABLE LENGTH TOLERANCES AND FANOUT LENGTH TOLERANCES  
ACCORDING TO SYLEX STANDARD [1-S-8000](#)
- 7 - TRACEBILITY LABEL ON THE CABLE CONTAINS SERIAL NUMBER,  
DATE OF PRODUCTION AND ASSEMBLY LENGTH
- 8 - TYPE OF POLARITIES ACCORDING TO [SPECIFICATION](#)

**ORDERING CODE**

**P12X-XXX-xxx**

- xxx cable length [050 = 50m, 001 = 1m]
- A - Polarity A, B - Polarity B, C - Polarity C
- F MTP(F) 12F, M MTP(M) 12F, J MTP(F) PRO 12F, P MTP(M) PRO 12F
- F MTP(F) 12F, M MTP(M) 12F, J MTP(F) PRO 12F, P MTP(M) PRO 12F
- 9 OS2, 3 OM3, 4 OM4, 5 OM5
- 12 12F
- P Patch cable

REVISION-DATE: A - 04.06.2019	CHANGE:	DRAWN BY, DATE: P. Gašpár 2019/06/04	TITLE: 12f 1xMTP - 1xMTP Patch cable		
New drawing		CHECKED BY, DATE: Pavlov/Matúš			
REVISION-DATE:	CHANGE:	APPROVED BY, DATE: I.Brestovanská	PRODUCT SPECIFICATION: -	DIMENSIONS IN MM UNLESS SPECIFIED	SCALE: NO SCALE
REVISION-DATE: X - DD.MM.YYYY	CHANGE:	PRODUCT NUMBER: P12X-XXX-xxx	DRAWING NUMBER: -	SHEET NO. 1 of 1	
		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SYLEX s.r.o AND ANY USE WITHOUT PRIOR WRITTEN PERMISSION IS PROHIBITED			SIZE A3