



NOTES :

- 1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN
- 2 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM
- 3 - OM3, OM4, OM5 - IL<0.35dB , RL>20dB , 850nm & 1300nm
OS2 - IL<0.35dB, RL>50dB, 1310nm & 1550nm

IL CONNECTOR VALUE ACCORDING IEC 61300-3-4 method B
RL CONNECTOR VALUE ACCORDING IEC 61300-3-6
- 4 - VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35.
END FACE GEOMETRY ACCORDING TO TELCORDIA GR-326
- 5 - ASSEMBLY WITH LENGTH BELOW 50MTRS PACKED IN SEALED PE BAG,
BULK PACK IN OUTER CARDBOARD BOX.
LONGER ASSEMBLY THEN 50MTRS COILED ON CARDBOARD REEL,
INSERTED IN CARDBOARD BOX ACCORDING TO SYLEX STANDARD [1-S-0011](#)
- 6 - CABLE LENGTH TOLERANCES AND FANOUT LENGTH TOLERANCES
ACCORDING TO SYLEX STANDARD [1-S-8000](#)
- 7 - PULLING SYSTEM ON ONE SIDE IS PART OF THE ASSEMBLY (NOT SHOWN)
- 8 - TRACEBILITY LABEL ON THE CABLE CONTAINS SERIAL NUMBER,
DATE OF PRODUCTION AND ASSEMBLY LENGTH
- 9 - TYPE OF POLARITIES ACCORDING TO [SPECIFICATION](#)

ORDERING CODE

X72X-XXX-xxx

- xxx cable length [050 = 50m, 001 = 1m]
- A - Polarity A, B - Polarity B, C - Polarity C
- F MTP(F) 12F, M MTP(M) 12F, J MTP(F) PRO 12F, P MTP(M) PRO 12F
- F MTP(F) 12F, M MTP(M) 12F, J MTP(F) PRO 12F, P MTP(M) PRO 12F
- 9 OS2, 3 OM3, 4 OM4, 5 OM5
- 72 72F
- T trunk, G trunk with grommet*
- * SHOWN TRUNK VERSION WITH GROMMET [G]

REVISION-DATE: A - 04.06.2019 CHANGE: New drawing	DRAWN BY, DATE: P. Gašpár 2019/06/04	TITLE: 72f 6xMTP - 6xMTP Duralino Trunk		
REVISION-DATE: _____ CHANGE: _____	CHECKED BY, DATE: Pavlov/Matúš	APPROVED BY, DATE: I. Brestovanská	PRODUCT SPECIFICATION: -	DIMENSIONS IN MM UNLESS SPECIFIED
REVISION-DATE: X - DD.MM.YYYY CHANGE: _____	APPROVED BY, DATE: I. Brestovanská	PRODUCT NUMBER: X72X-XXX-xxx	DRAWING NUMBER: -	SCALE: NO SCALE
		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SYLEX s.r.o AND ANY USE WITHOUT PRIOR WRITTEN PERMISSION IS PROHIBITED		SHEET NO. 1 of 1
				SIZE A3