

## IP LC duplex inline adaptor

### Basic characteristics

- ▲ LC duplex inline adapter available in various colour versions of the LC duplex adaptor inside.
- ▲ IP 68 Water immersion and Dust protection
- ▲ Suitable for connection of two IP LC duplex connectors
- ▲ Fixation with nut and compression seal into the designated cutout
- ▲ Chemical and UV resistance
- ▲ Interchangeable with other industrial LC adaptors per IEC 61076-3-106



### Applications

- |                     |                    |
|---------------------|--------------------|
| ▲ Harsh environment | ▲ Medical          |
| ▲ Fiber to Antenna  | ▲ Oil and Gas      |
| ▲ Military          | ▲ Transport        |
| ▲ Broadcasting      | ▲ Renewable energy |

| <b>Temperature range</b>                                   |                      |
|--|----------------------|
| Operating Temperature                                      | (-40°C/+70°C)        |
| <b>Adaptor parameters</b>                                  |                      |
| Compliance   | Telcordia GR-326     |
| Colour of IP adaptor housing                               | Black                |
| Colour of LCD adaptor housing                              | Blue / Green / Beige |
| Insertion Loss   | <0.20dB              |
| Repeatability  | <0.20dB (500 times)  |
| <b>Packaging</b>   |                      |
| Each adaptor in sealed PE bag, bulk pack in cardboard box. |                      |

\*Specifications are subject to change without notice

**For more information, contact our sales team at [sales@sylex.sk](mailto:sales@sylex.sk)**